



**Energy Wise
Lighting, Inc.** | T5HO-4-P

Premium Lens Enclosed
T5HO 4-Lamp Fixture

Applications:

Warehouses, manufacturing, metal shops, workshops,
food processing, retail, aircraft hangers

Features:

- Uses 50% less energy than HID's
- Color rendering index of 85
- Instant on/off
- 30,000 hour lamp life
- Silent operation
- Pre-lamped
- Positive friction lens cover and door
- 95% mirrored reflector



Models Available: 2-lamp, 3-lamp, 4-lamp, 5-lamp, 6-lamp

Replaces: 400 watt metal halides and 400 watt high pressure sodium fixtures

Specifications:

Model: 4-lamp, T5HO-4-P

Weight: 14 lbs.

Fixture body: .04" brushed aluminum

Dimensions: 3"D x 16"W x 47"L (add 4" for optional sensor)

Operating Temperature: 20F to 120F ambient temperature

Ballast Specs: Power Factor >.98; THD <10%, Program Start, U.L. Listed, Instant Restrike,
Ballast Frequency >20,000 Hz., Ballast Crest Factor <1.7, Voltage range 120-277, 50/60 Hz. Ballast Factor 1.0,
End of Life Protection, Flicker <3%. Start time .9 – 1.0 seconds, 347 to 480v ballasts available.

Reflector: one piece continuous 95% reflector

Lamps: 54 watt, 5000 kelvin standard, 85 CRI. Also available in 3000, 3500, 4100, 6500 kelvin.
Lamp life 30,000 hours

Occupancy sensor: adjustable time delay, 30 seconds to 20 minutes. Up to 45' mounting height
Operating temperature 14F to 160F. 50/60 hertz. 5 year warranty

Fixture Wattage: 4-lamps: 234 watts nominal. 188 to 250 watts, temperature dependent

Warranty: 2-year manufacturer's warranty on lamps, 5-year manufacturer's warranty on ballasts,
5-year warranty against all other defects, 5-year manufacturer's warranty on occupancy sensor.

*Savings based on energy savings from replacing a 400 watt metal halide fixture operating
10 hours per day, 6 days per week (\$0.10/KWH).

